



# Irrigation Tire and Wheel Solutions

We know irrigation tires and wheels.



The largest collection of irrigation tires and wheels ensures our products will get the job done.



Competitive prices



Excellent customer service



Extensive inventory



Premium Warranty



Reliable team





## IRRIGATION R1

- Irrigation Special Tire.
- Application to mobile irrigation system equipment.
- Good traction and self-cleaning performance.



Size	Load Index/ Ply-rating	TRA CODE	TUBE TYPE	TREAD DEPTH		Standard Rim	SECTION WIDTH		OVERALL DIAMETER		Load Capacity		Inflation Pressure	
				mm	inch		mm	inch	mm	inch	kgs	lbs	kpa	psi
11.2-24	6	R1	TT	33	1.30	W10	285	11.2	1105	43.50	1045	2300	180	26
14.9-24	6	R1	TT	26	1.00	W13	378	14.9	1265	49.80	1510	3329	140	20
14.9-24	8	R1	TT	26	1.00	W13	378	14.9	1265	49.80	1510	3329	140	20
11.2-38	6	R1	TT	25	0.98	W10	285	11.2	1448	57.00	1150	2535	180	26
11.2-38	8	R1	TT	25	0.98	W10	285	11.2	1448	57.00	1350	2976	250	36



## IRRIGATION R1 BD

- Non-directional tread pattern for equal traction in forward and reverse direction.
- Designed with a 0-degree bar angle for less slippage than conventional tread designs for reduced soil disturbance and rutting.
- For use on linear and pivot irrigation systems



Size	Load Index/ Ply-rating	TRA CODE	TUBE TYPE	TREAD DEPTH		Standard Rim	SECTION WIDTH		OVERALL DIAMETER		Load Capacity		Inflation Pressure	
				mm	inch		mm	inch	mm	inch	kgs	lbs	kpa	psi
11.2-24	6	R1	TT/TL	25	0.98	W10	285	11.2	1103	43.40	950	2090	180	26
11.2-24	6	R1	TT/TL	25	0.98	W10	285	11.2	1103	43.40	1150	2540	250	36
14.9-24	6	R1	TT/TL	25	0.98	W13	378	14.9	1265	49.80	1600	3520	180	26
14.9-24	8	R1	TT/TL	25	0.98	W13	378	14.9	1265	49.80	1850	4080	230	34
11.2-38	10	R1	TT	30	1.18	W10	285	11.2	1448	57.00	2000	4410	170	25



## IS4100

- Excellent traction in wet and muddy conditions in addition to outstanding self-cleaning properties
- Specifically developed for irrigation applications with pivot irrigators
- Long service life



Size	Load Index/ Ply-rating	TRA CODE	TUBE TYPE	TREAD DEPTH		Standard Rim	SECTION WIDTH		OVERALL DIAMETER		Load Capacity		Inflation Pressure	
				mm	inch		mm	inch	mm	inch	kgs	lbs	kpa	psi
280/85R24 (11.2R24)	115A8/ 115B	R1W	TL	41	1.6	10.00	285	11.2	1080	42.5	1215	2678	160	23
380/85R24 (14.9R24)	131A8/ 131B	R1W	TL	47	1.8	12.00	382	15.0	1273	50.0	1950	4300	160	23
320/85R38 (12.4R38)	129A8/ 126B	R1W	TL	43	1.7	11.00	319	12.6	1509	59.4	1850	4078	160	23



## TNR IRRI001

- Specially designed for mobile irrigation system equipment
- Valve guard
- Reverse mount available

**Surface finish:**

- Hot Dip Galvanized
- Paint
- Black



Size	Bolt Hole Dimension			Centre Bore (Inch)	Thickness				Offset		Tire Size
	Number	Diameter (Inch)	PC.D (Inch)		Rim		Disk		mm	inch	
					mm	inch	mm	inch			
W8x24	8	0.65	8	6	4	0.157	6	0.236	50.8	2	11.2-24
	8	0.65	8	6	4	0.157	6	0.236	0	0	
W10x24	8	0.65	8	6	4	0.157	6	0.236	50.8	2	11.2-24
	8	0.65	8	6	4	0.157	6	0.236	0	0	
W12x24	8	0.65	8	6	4	0.157	6	0.236	70	2.75	13.6-24, 14.9-24
	8	0.65	8	6	4	0.157	6	0.236	0	0	
	8	0.65	8	6	4	0.157	6	0.236	50.8	2	
W15Lx24	8	0.65	8	6	4	0.157	6	0.236	0	0	16.9-24
W10x38	8	0.65	8	6	4	0.157	6	0.236	44	1.75	11.2-38
	8	0.65	8	6	4	0.157	6	0.236	62	2.44	
W10x38	9	0.65	9.5	7.93	4	0.157	6	0.236	44	1.75	11.2-38
8.25X22.5	8	0.65	8	6	4	0.157	6	0.236	0	0	11-22.5
8.25X24.5	8	0.65	8	6	4	0.157	6	0.236	0	0	11-24.5





# Wheel Assembly

## Advantages of purchasing complete tire and wheel assemblies



### Save Fitting Cost

The large volume of assemblies we do every day gives us a price advantage in assembly costs.



### Save Freight Cost

We ship more assembled than separately.



### Quality Warranty

All assemblies are done with strict quality control, and come with warranty.



### Supply of Every Component

Complete wheel tire and wheel assemblies arrive at the customer inflated, with all mobility devices and accessories installed, ready to bolt onto the hub and drive away.

