

# **MICHELIN<sup>®</sup>** **X<sup>®</sup>TRA LOADPROTECT<sup>™</sup>**



***EASY LIFE IN HARD CONDITIONS***



RIGID DUMP TRUCKS



# MICHELIN® X®TRA LOADPROTECT™

## EXCELLENT PROTECTION IN HARD, SHARP GROUND CONDITIONS




**8-11%**  
HIGHER PAY LOAD<sup>1,2</sup>



**MORE DISTANCE  
IN AN HOUR<sup>3</sup>**



**+7-8%**  
WEAR LIFE<sup>4,5</sup>



### CORROSION- PROOF CABLES

Steel encapsulated by rubber prevents corrosion spread, thus increasing aggression resistance

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist./hour km mile	TKPH TMPH	Tread depth mm 32rd
X TRA LOAD PROTECT B *** E4 18.00R33 Tubeless	769976 21909	34 21.1 if load per tire <=10.9 t 31 19.3 if load per tire >10.9 t	301 206	63 79.4
X TRA LOAD PROTECT A4 *** E4 18.00R33 Tubeless	646057 89058	22 13.7 if load per tire <=10.9 t 20 12.4 if load per tire >10.9 t	194 133	63 79.4
X TRA LOAD PROTECT B *** E4 24.00R35 Tubeless	488798 67386	34 21.1 if load per tire <=18.5 t 31 19.3 if load per tire >18.5 t	503 345	70 88.2
X TRA LOAD PROTECT A4 *** E4 24.00R35 Tubeless	388190 05723	22 13.7 if load per tire <=18.5 t 20 12.4 if load per tire >18.5 t	320 219	70 88.2

<sup>1</sup> Compared to the Bridgestone® VMTP and VRLS tires and MICHELIN® X®QUARRY™ S tires in size 18.00R33. Actual results may vary. (Sources: Bridgestone® OTR 2018 Data Book and MICHELIN® 2017 Data Book.)

<sup>2</sup> Compared to the same size in Bridgestone® VMTP and VRLS – Source Bridgestone® OTR Databook 2016 and MICHELIN® X®QUARRY™ S – Source Michelin® Databook 2017.

<sup>3</sup> Compared to MICHELIN® X®QUARRY™ S tires. Actual results may vary.

<sup>4</sup> Compared to MICHELIN® X®QUARRY™ S tires in size 18.00R33 and based on field tests measurements and FARO-method measurements certified by the Michelin® Center of Technology. Actual results may vary.

<sup>5</sup> Compared to the same size in MICHELIN® X®QUARRY™ S, field tests measurements certified by the Michelin® Center of Technology, from 2015 to 2017.

